

Ultrasonic Film Splicer Model 3001



The Model 3001 adapts to all major motion picture microfilm formats - Super 8 to 35mm (with changeable film register plates). Size: 8" x 12.5" x 6.5" (20.3 x 31.8 x 16.5cm) Weight 16 lbs. (7.30 Kg).

Splicer Features

- Archival Splices
- No Emulsion Scraping
- No Tape-No Cement- No consumables are required. A strong, permanent weld in seconds.
- Easy To Operate- Film always remains in perfect alignment.
- Thin Splice- All Metric Splicer, Inc. ultrasonic film splicers fuse with a weld of nearly single-film thickness.
- Darkroom or Daylight- Splicer is designed for daylight or darkroom use...splicing short ends eliminates a waste problem. Will not fog raw stock.
- No Special Installation- Portable...just plug in...2 amps, 50-60 Hz. Multi-voltage input transformer (100-240V) is standard.
- Special Applications- Can be adapted to custom formats to meet special requirements.
- Sample Splices- Upon request, Metric Splicer, Inc will send a sample splice for inspection, or will make splices from furnished film. No obligations.



CHINA SYSTEM COMPANY LTD.

INTERNATIONAL DIGITAL IMAGING SYSTEMS CO. (wholly owned subsidiary)

Head Office:
Suite 2913-15, Hong Kong Plaza,
188 Connaught Road West, Hong Kong
Tel: (+852) 2548-6112
Fax: (+852) 2559-9469
Website: www.chinasystem.com.hk
e-mail: info@chinasystem.com.hk

Shanghai Office:
Unit 308, 3/F, Building 3, No.499 Kanghua Road,
Zhongtian Science Park East Park,
Pudong District, Shanghai, 201315, China
Tel: (021)-58305536 / 58305772 / 36320539*803
Fax: (021)-50686293
E-mail: jacky@generule.com